

CONTINUOUS ROLL 316 STAINLESS STEEL CABLE TIES

Hayata's continuous roll stainless steel cable ties are for applications that require various cut-to-length sizes on the job. This allows the operator to pull the required tie length and cut based on specified bundle size.

Heads are then easily slipped on to complete the tie.

- 150 Lb. & 300 Lb. tensile strength, are stocked.
- 450 Lb. & 900 Lb. tensile strength are available. Please call for minimum order requirements.



Continuous Roll 316 Stainless Steel

| COATED Part No. | LENGTH | | WIDTH | | THICKNESS UNCOATED | | MAXIMUM BUNDLE | | PACKAGING |
|--------------------|--------|-----|-------|-----|--------------------|------|----------------|-----|--------------|
| | Ft | M | In | mm | In | mm | In | mm | Roll per Box |
| TBC150LB/50 | 164 | 50 | .18 | 4.6 | 0.01 | 0.26 | Any | Any | 1 |
| TBC300LB/50 | 164 | 50 | .31 | 7.9 | 0.01 | 0.26 | Any | Any | 1 |
| TBC150LB/10 | 328 | 100 | .18 | 4.6 | 0.01 | 0.26 | Any | Any | 1 |
| TBC300LB/100 | 328 | 100 | .31 | 7.9 | 0.01 | 0.26 | Any | Any | 1 |

Hayata Application Tools: CT-3, CT-5, CT-7, BT2000, BT9000, BT14000

Applications: General. User can determine length of tie.

To figure the length to use on each application, follow this formula:

$$[(\text{Diameter} \times 3.14) + 2.5 \text{ inches}] (64 \text{ mm})$$

Heads for Continuous Roll • 316 SS

| Heads for Uncoated Part No. | Quantity Per Box |
|-----------------------------|------------------|
| TBC150LBHEAD | 100 |
| TBC300LBHEAD | 100 |

Note: Heads are to be used with matching continuous rolls listed. ABS Type Approval.