Coated Stainless Steel

CABLE TIES & BANDING

Coated stainless steel TIES AND BANDING applied to cable tray

Stainless steel
Easy-Entry™ TAGS
applied to cable, valves
and enclosures



Stainless steel and Monel® BANDING applied to pier pilings and strakes

Why Hayata?

- First to introduce fully coated stainless steel cable ties.
- Highest Tensile Strengths in the industry for coated ties (the Strongest Around!).
- Offered in a wide variety of colors for easy identification.
- New EZID Ties (for inspectors to identify the ties) are made of SS (uncoated heads).









Hayata Coated Cable Ties & Banding Features

- Fully coated ties including the head
- Higher tie tensile strength compared to other brands (per UL62275)
- Anti-vibration
- Salt-spray resistant
- UV resistant
- Low Smoke
- Halogen-Free

- Corrosion resistant
- Extreme temperatures
- Prevents dissimilar metal corrosion
- Long-term bundling
- Strengthens physical infrastructure for harsh environments
- Edge Protections with rounded edges

To Order: US Toll Free: 833-862-1668 • www.Hayata.com • sales@Hayata.com

Coated Stainless Steel

CABLE TIES

Sizes range from 3/16" (4.6mm) to 5/8" (15mm).

Tensile loads of 200, 300, 425 and 500 lbs.

Hayata delivers high strength and reliability in the harshest, most corrosive environments.











Hayata introduced the first fully coated tie into the market place in 2005. While other brands copied this, no one has equaled our ties performance.

Hayata's Tensile Strengths on Coated Ties exceeds that of all competitors per UL62275.

These ties are ready to secure products in the harshest environments of todays oil & gas, shipbuilding and petro chemical industries.



Today, we continue to **coat the entire tie** as our standard, including the head, because corrosion does not only attack the strap. If there is an engineering requirement for special colors or coating requirements, please contact us as we offer full line of colors including red, blue, green, yellow and white



Hayata banding holds tight in the harshest offshore environments



BANDING

Independent lab (ASTM E8-04) reports prove Hayata's stainless steel banding is the strongest in the industry.

Available in widths ranging from 1/4" (7mm) to 5/8" (15.8mm).

Wide range of stainless steel grades, lengths and buckle type to match your application.



To Order: US Toll Free: 833-862-1668 • www.Hayata.com • sales@Hayata.com



Coated Stainless Steel CABLE TIES

Fully coated ties – including the head









Roller Ball Ties • 200 Lb. Standard • 316 SS

COATED	LEN	GTH	WID	TH		(NESS)ATED		(NESS ATED	DIAMETER		BAG Wt.	PACKAGI Ties Bags Per Per		ING Bag
Part No.	In	mm	In	mm	In	mm	In	mm	Min	Max	lbs	Bag	Box	(LxWmm)
TBC100C	4	100	0.18	4.6	0.01	0.26	0.01	0.33	0.5" (12.7)	1" (25)	0.37	100	50	200x150
TBC150C	6	150	0.18	4.6	0.01	0.26	0.01	0.33	0.5" (12.7)	1.5" (39)	0.46	100	50	200x150
TBC200C	8	200	0.18	4.6	0.01	0.26	0.01	0.33	0.5" (12.7)	2" (50)	0.57	100	50	255x150
TBC360C	14	360	0.18	4.6	0.01	0.26	0.01	0.33	0.5" (12.7)	4" (100)	0.92	100	35	410x150
TBC520C	20.5	520	0.18	4.6	0.01	0.26	0.01	0.33	0.5" (12.7)	6" (150)	1.23	100	25	580x150
TBC680C	26.5	680	0.18	4.6	0.01	0.26	0.01	0.33	0.5" (12.7)	8" (200)	1.54	100	15	430x230
TBC840C	33	840	0.18	4.6	0.01	0.26	0.01	0.33	0.5" (12.7)	10" (250)	1.91	100	10	430x230
TBC1000C	39	1000	0.18	4.6	0.01	0.26	0.01	0.33	0.5" (12.7)	12" (300)	2.29	100	10	430x230
TBC1200C	47	1200	0.18	4.6	0.01	0.26	0.01	0.33	0.5" (12.7)	14" (365)	2.73	100	10	430x230
TBC1400C	55	1400	0.18	4.6	0.01	0.26	0.01	0.33	0.5" (12.7)	17" (425)	3.17	100	10	430x230

Roller Ball Ties • 300 Lb. Heavy Duty • 316 SS

TBC200HC	8	200	0.31	7.9	0.01	0.26	0.01	0.33	0.5" (12.7)	2" (50)	1.12	100	25	265x150
TBC360HC	14	360	0.31	7.9	0.01	0.26	0.01	0.33	0.5" (12.7)	4" (100)	1.69	100	25	420x150
TBC520HC	20.5	520	0.31	7.9	0.01	0.26	0.01	0.33	0.5" (12.7)	6" (150)	2.2	100	20	580x150
TBC680HC	26.5	680	0.31	7.9	0.01	0.26	0.01	0.33	0.5" (12.7)	8" (200)	2.82	100	10	430x230
TBC840HC	33	840	0.31	7.9	0.01	0.26	0.01	0.33	0.5" (12.7)	10" (250)	3.39	100	5	430x230
TBC1000HC	39	1000	0.31	7.9	0.01	0.26	0.01	0.33	0.5" (12.7)	12" (300)	3.89	100	5	430x230
TBC1200HC	47	1200	0.31	7.9	0.01	0.26	0.01	0.33	0.5" (12.7)	14" (365)	4.49	100	5	430x230
TBC1400HC	55	1400	0.31	7.9	0.01	0.26	0.01	0.33	0.5" (12.7)	17" (425)	5.15	100	5	430x230

Roller Ball Ties • 425 Lb. Heavy Duty • 316 SS

TBC200XHDC	8	200	0.5	12.5	0.02	0.35	0.02	0.47	1" (25.4)	2" (50)	1.54	100	10	255x230
TBC290XHDC	11.5	290	0.5	12.5	0.02	0.35	0.02	0.47	1" (25.4)	3.1" (80)	2.2	100	10	340x230
TBC360XHDC	14	360	0.5	12.5	0.02	0.35	0.02	0.47	1" (25.4)	3.9" (100)	2.86	100	10	420x230
TBC520XHDC	20.5	520	0.5	12.5	0.02	0.35	0.02	0.47	1" (25.4)	5.9" (150)	3.96	100	10	430x300
TBC680XHDC	26.5	680	0.5	12.5	0.02	0.35	0.02	0.47	1" (25.4)	7.9" (200)	5.28	100	5	430x300
TBC840XHDC	33	840	0.5	12.5	0.02	0.35	0.02	0.47	1" (25.4)	9.8" (250)	6.38	100	5	430x300
TBC1000XHDC	39	1000	0.5	12.5	0.02	0.35	0.02	0.47	1" (25.4)	11.8" (300)	7.48	100	5	430x300

Applications & Approvals: General Bundling, Packaging, cUL Listed, DNV Approved, ABS Type Approval, Lloyd's Type.

Roller Ball Ties • 500 Lb. Heavy Duty • 316 SS

CUL US TED US TANK	ABS.
--------------------	------

TBC457XXHDC	18	457	.625	15.88	0.01	0.35	0.02	0.45	1" (25.4)	4.3" (109)	0.9	50	20	380x230
TBC610XXHDC	24	610	.625	15.88	0.01	0.35	0.02	0.45	1" (25.4)	6.2" (158)	1.2	50	20	380x230
TBC762XXHDC	30	762	.625	15.88	0.01	0.35	0.02	0.45	1" (25.4)	8.1" (206)	1.4	50	20	510x230

Applications & Approvals: General Bundling, Packaging, ABS Type Approval, cUL Listed.




EZID TIES

EZID ties come with an



uncoated head and a coated tie strap. Add -EZID to the end of a coated tie's part number to make it an EZID tie. *Example:* TBC1000C-EZID





COATED CABLE MARKING TIES

Hayata's highly durable coated stainless steel cable ties are a great option for high-volume marking and maintenance operations. These fully coated ties resist fading due to weather and harsh environments.

- Fully coated ties including the head
- Prevents dissimilar metal corrosion
- Edge Protections with rounded edges
- ABS Type Approval

Corrosion resistant

- Salt-spray resistant
- UV resistant
- Low Smoke
- Halogen-Free



NOTE: Add color suffix to any coated tie product (see previous page) to get the color and size tie you require. Example: TBC100C-YW

COATED BANDING



Hayata Super Coated Band (Black) 316 SS • 82.5 ft.

COATED	THICKNESS		WII	DTH	WEI	GHT	BUCKLE	BUCKLE TYPE	PACKAGING
Part No.	In	In mm		In mm Lb Kg		Kg	TYPE	Part No.	
CB3162	.048	1.22	1/4	6.35	3	1.4		CBWS3162	
CB3163	.048	1.22	3/8	9.53	2.75	1.25	Wing	CBWS3163	10 Rolls
CB3164	.048	1.22	1/2	12.7	3.75	1.7	Seal	CBWS3164	Per Box
CB3165	.048	1.22	5/8	15.88	4.4	2	316 SS	CBWS3165	
CB3166	.048	1.22	3/4 19		5.2	2.36		CBWS3166	



Hayata Super Coated Band 316 SS • Custom Lengths

	COATED	COATED LENGTH		WIDTH		THICKNESS COATED		MAX BUNDLE DIAMETER		BAG Wt.	PACKAGING Ties Bags Per Per Bag		GING Bag
	Part No.	In	mm	In	mm	In	mm	Min	Max	Lb	Bag	Box	(LxWmm)
	CB3165-18WBKL	18	457	5/8	15.88	.048	1.22	4.8	122	1	25	4	380x230
	CB3165-24WBKL	24	610	5/8	15.88	.048	1.22	6.7	170	1.3	25	4	380x230
I	CB3165-30WBKL	30	762	5/8	15.88	.048	1.22	8.6	218	1.6	25	4	510x230



Hayata Application Tools: BT200, RT400, BTX8000

Applications: Marine, Corrosive, Vibration

Approval: DNV Approved, ABS Type Approval, PPA Material available upon request

To Order: US Toll Free: 833-862-1668 • www.Hayata.com • sales@Hayata.com