

## ZIG ZAG STAINLESS STEEL CABLE TIES

Hayata's Zig Zag stainless steel cable ties are designed to maintain tension on hard surfaces such as a pipe or steel pole. All Zig Zag ties are 316 grade stainless steel for excellent resistance to temperature extremes, corrosion, weather, chemicals, salt sprays and UV radiation.

- Resistance to chemicals and salt sprays
- Non-toxic, halogen-free

*Zig Zag cable ties are designed to maintain tension on hard surfaces such as a pipe or steel poles*



### Zig Zag Ties • 150 Lb. • 316 SS

UNCOATED Part No.	COATED Part No.	LENGTH		WIDTH		THICKNESS UNCOATED		THICKNESS COATED		BUNDLE DIAMETER		BAG Wt. lbs	PACKAGING		
		In	mm	In	mm	In	mm	In	mm	Min	Max		Ties Per Bag	Bags Per Box	Bag (LxWmm)
TBC200Z	TBC200ZC	8	200	0.18	4.5	0.01	0.26	0.01	0.33	2"	50	0.57	100	50	255X150
TBC360Z	TBC360ZC	14	360	0.18	4.5	0.01	0.26	0.01	0.33	4"	100	0.92	100	35	410X150
TBC520Z	TBC520ZC	20.5	520	0.18	4.5	0.01	0.26	0.01	0.33	6"	150	1.23	100	25	580X150
TBC680Z	TBC680ZC	26.5	680	0.18	4.5	0.01	0.26	0.01	0.33	8"	200	1.54	100	15	430X230
TBC840Z	TBC840ZC	33	840	0.18	4.5	0.01	0.26	0.01	0.33	10"	250	1.91	100	10	430X230
TBC1000Z	TBC1000ZC	39	1000	0.18	4.5	0.01	0.26	0.01	0.33	12"	300	2.29	100	10	430X230
TBC1200Z	TBC1200ZC	47	1200	0.18	4.5	0.01	0.26	0.01	0.33	14"	365	2.73	100	10	430X230
TBC1400Z	TBC1400ZC	55	1400	0.18	4.5	0.01	0.26	0.01	0.33	17"	425	3.17	100	10	430X230



### Zig Zag Ties • 300 Lb. • 316 SS

UNCOATED Part No.	COATED Part No.	LENGTH		WIDTH		THICKNESS UNCOATED		THICKNESS COATED		BUNDLE DIAMETER		BAG Wt. lbs	PACKAGING		
		In	mm	In	mm	In	mm	In	mm	Min	Max		Ties Per Bag	Bags Per Box	Bag (LxWmm)
TBC200HZ	TBC200HZC	8	200	0.31	4.5	0.01	0.26	0.01	0.33	2"	50	1.12	100	25	255X150
TBC360HZ	TBC360HZC	14	360	0.31	4.5	0.01	0.26	0.01	0.33	4"	100	1.69	100	20	410X150
TBC520HZ	TBC520HZC	20.5	520	0.31	4.5	0.01	0.26	0.01	0.33	6"	150	2.2	100	15	580X150
TBC680HZ	TBC680HZC	26.5	680	0.31	4.5	0.01	0.26	0.01	0.33	8"	200	2.82	100	10	430X230
TBC840HZ	TBC840HZC	33	840	0.31	4.5	0.01	0.26	0.01	0.33	10"	250	3.39	100	5	430X230
TBC1000HZ	TBC1000HZC	39	1000	0.31	4.5	0.01	0.26	0.01	0.33	12"	300	3.89	100	5	430X230
TBC1200HZ	TBC1200HZC	47	1200	0.31	4.5	0.01	0.26	0.01	0.33	14"	365	4.49	100	5	430X230
TBC1400HZ	TBC1400HZC	55	1400	0.31	4.5	0.01	0.26	0.01	0.33	17"	425	5.15	100	5	430X230

**Hayata Application Tools:** CT-3, CT-5, CT-7, BT2000, BT9000, BT14000 or By Hand  
**Applications:** Where tension on solid object must be maintained – Pipes, Poles, etc.  
**Approvals:** ABS Type Approval



**To Order:** US Toll Free: 833-862-1668 • [www.Hayata.com](http://www.Hayata.com) • [sales@Hayata.com](mailto:sales@Hayata.com)