


Coated Cable Marking Ties

Hayata's highly durable coated stainless steel cable ties are a great option for high-volume marking and maintenance operations. These fully coated ties resist fading due to weather and harsh environments.

STANDARD COLORS



- Available in 200 Lb, 300 Lb, 425 Lb and 500 Lb
- Easy visual identification
- · All stainless steel ties are fully coated
- Pre-cut lengths come with installed roller ball buckle
- Allows tag to be spun on pipe for easier inspection
- High tensile strength exceeds industry standards
- Wide variety of lengths and standard or special order colors
- ABS Type Approval



Part No.		LENGTH		WIDTH		COL	PACKAGING		
200 Lb	300 Lb	In	mm	In	mm	Standard	Special Order Colors		Ties per Bag
TBC200C	TBC200HC	18	457	1/2	12.7	Blue - BE	Brown - BN	Pink - PK	
TBC360C	TBC360HC	22	558	1/2	12.7	Green - GN	Grey - GY	Purple - PE	
TBC520C	TBC520HC	27	680	1/2	12.7	Red - RD	Light Blue - LB	Tan - TN	100
TBC680C	TBC680HC	30	762	1/2	12.7	White - WE	Orange - OE		
TBC840C	TBC840HC	40	1,016	1/2	12.7	Yellow - YW			

Aluminum Ties Lighter-weight alternative to stainless steel ties

- Non-toxic, halogen-free & non-flammable
- Excellent chemical & UV resistance
- Uncoated temperature range: -112°F (-80°C) to 1000°F (538°C)
- Coated temperature range: -112°F (-80°C) to 302°F (150°C)
- Self-locking mechanism speeds installation, lowering overall installed cost
- Sharp edges and burrs are removed to protect installation and bundle

Roller Ball Ties • 50 Lb. • Aluminum



UNCOATE	D	COATED	LENGTH		WIDTH		THICKNESS		MAX BUNDLE		BAG	PACKAGING Ties Bags		
										IETER	Wt.	Per	Per	Bag
Part No.		Part No.	In	mm	In	mm	In	mm	In	mm	Lb	Bag	Box	(LxWmm)
TBC150AL	-	TBC150ALC	6"	150	0.31	7.9	0.01	0.03	1.5	39	0.24	100	25	200X150
TBC200AL	-	TBC200ALC	8"	200	0.31	7.9	0.01	0.03	2	51	0.27	100	25	255X150
TBC360AL	-	TBC360ALC	14"	360	0.31	7.9	0.01	0.03	4	102	0.36	100	20	420X150
TBC520AL	•	TBC520ALC	20.5"	520	0.31	7.9	0.01	0.03	6	151	0.52	100	20	580X150

Hayata Application Tools: CT-3, CT-5, CT-7, BT15000 Applications: Marine, Defense **Approval:** ABS Type Approval