

## DOUBLE LOOP TIES

Double-loop stainless steel cable ties for twice the holding power



### Double Loop Ties • 800 Lb. • 316 SS



UNCOATED Part No.	COATED Part No.	LENGTH		WIDTH		THICKNESS UNCOATED		THICKNESS COATED		MAX BUNDLE DIAMETER		BAG Wt. Lb	PACKAGING		
		In	mm	In	mm	In	mm	In	mm	Min	Max		Ties Per Bag	Bags Per Box	Bag (LxWmm)
TBC470H-DL	TBC470H-DLC	18.5	470	0.31	7.9	0.01	0.26	0.013	0.33	2	51	2.09	100	20	580x150
TBC711H-DL	TBC711H-DLC	28	711	0.31	7.9	0.01	0.26	0.013	0.33	4	102	3.19	100	10	430x230
TBC863H-DL	TBC863H-DLC	34	863	0.31	7.9	0.01	0.26	0.013	0.33	5	127	3.85	100	10	430x230
TBC1016H-DL	TBC1016H-DLC	40	1016	0.31	7.9	0.01	0.26	0.013	0.33	6	152	4.44	100	5	430x230

**Hayata Application Tools:** CT-3, CT-5, CT-7, BT2000, BT9000, BT15000 or By Hand  
**Applications:** General Bundling, Heavy Corrosive Environment, Short Circuit Tested  
**Approvals:** ABS Type Approval, DNV Approved



### Double Loop Ties • 1200 Lb. • 316 SS



UNCOATED Part No.	COATED Part No.	LENGTH		WIDTH		THICKNESS UNCOATED		THICKNESS COATED		MAX BUNDLE DIAMETER		BAG Wt. Lb	PACKAGING		
		In	mm	In	mm	In	mm	In	mm	Min	Max		Ties Per Bag	Bags Per Box	Bag (LxWmm)
TBC749XHD-DL	TBC749XHD-DLC	29.5	749	1/2	12.5	0.02	0.35	0.018	0.47	2	51	6.16	100	5	430x300
TBC1054XHD-DL	TBC1054XHD-DLC	41.5	1054	1/2	12.5	0.02	0.35	0.018	0.47	4	102	8.47	100	5	430x300
TBC1359XHD-DL	TBC1359XHD-DLC	53.5	1359	1/2	12.5	0.02	0.35	0.018	0.47	5	127	11.22	100	5	430x300

**Hayata Application Tools:** CT-3, CT-7, BT15000 or By Hand  
**Applications:** General Bundling, Heavy Corrosive Environment, Short Circuit Tested  
**Approvals:** ABS Type Approval, DNV Approved



### Double Loop Ties • 1250 Lb. • 316 SS



UNCOATED Part No.	COATED Part No.	LENGTH		WIDTH		THICKNESS UNCOATED		THICKNESS COATED		MAX BUNDLE DIAMETER		BAG Wt. Lb	PACKAGING		
		In	mm	In	mm	In	mm	In	mm	Min	Max		Ties Per Bag	Bags Per Box	Bag (LxWmm)
TBC749XXHD-DL	TBC749XXHD-DLC	29.5	749	5/8"	15.88	0.02	0.35	0.018	0.47	4	102	8.8	50	10	510x230
TBC1054XXHD-DL	TBC1054XXHD-DLC	41.5	1054	5/8"	15.88	0.02	0.35	0.018	0.47	5	127	12.43	50	10	510x230
TBC1359XXHD-DL	TBC1359XXHD-DLC	53.5	1359	5/8"	15.88	0.02	0.35	0.018	0.47	6	152	15.95	50	10	510x230

**Hayata Application Tools:** CT-7, BT15000 or By Hand  
**Applications:** General Bundling, Heavy Corrosive Environment, Short Circuit Tested  
**Approvals:** ABS Type Approval, DNV Approved