


LADDER TIES

Hayata ladder style cable ties can be used in virtually all indoor, outdoor and underground (including direct burial) applications. They are well-suited for network bundling of data and power cables. Their high strength, non-flammability and rounded edges provide the definitive support for network cables.

All coated ties are 316 grade stainless steel for excellent resistance to temperature extremes, corrosion, weather, chemicals, salt sprays and UV radiation.


- Non-toxic, halogen-free
- No water absorption
- Non-flammable
- Uncoated temperature range: -112°F (-80°C) to 1000°F (538°C)
- Coated temperature range: -112°F (-80°C) to 302°F (150°C)
- Excellent chemical and UV resistance
- Can be used for air handling spaces
- Radiation resistance: 2 x 10⁸ rads
- Sharp edges and burrs have been removed to protect installation and bundle



Ladder Ties • 250 Lb. Standard • 316 SS



UNCOATED Part No.	COATED Part No.	LENGTH		WIDTH		THICKNESS UNCOATED		THICKNESS COATED		BUNDLE DIAMETER		BAG Wt. lbs	PACKAGING		
		In	mm	In	mm	In	mm	In	mm	Min	Max		Ties Per Bag	Bags Per Box	Bag (LxWmm)
KST225/7	KST225/7C	9	225	.25	7	0.01	0.3	0.02	0.41	2.75"	70	0.34	100	25	150x280
KST300/7	KST300/7C	12	300	.25	7	0.01	0.3	0.02	0.41	3.74"	95	0.97	100	25	150x350
KST400/7	KST400/7C	15.75	400	.25	7	0.01	0.3	0.02	0.41	4.45"	113	1.21	100	20	150x410
KST450/7	KST450/7C	17.75	450	.25	7	0.01	0.3	0.02	0.41	4.53"	115	1.43	100	20	150x500
KST600/7	KST600/7C	24	610	.25	7	0.01	0.3	0.02	0.41	5.91"	150	1.74	100	5	230x430
KST700/7	KST750/7C	29.5	750	.25	7	0.01	0.3	0.02	0.41	7.87"	200	2.20	100	5	230x430
KST800/7	KST800/7C	39.25	1000	.25	7	0.01	0.3	0.02	0.41	11.81"	300	3.08	100	5	230x430



Ladder Ties • 450 Lb. Heavy Duty • 316 SS



UNCOATED Part No.	COATED Part No.	LENGTH		WIDTH		THICKNESS UNCOATED		THICKNESS COATED		BUNDLE DIAMETER		BAG Wt. lbs	PACKAGING		
		In	mm	In	mm	In	mm	In	mm	Min	Max		Ties Per Bag	Bags Per Box	Bag (LxWmm)
KST225/12	KST225/12C	9	225	.5	12	0.01	0.35	2.75	60	2.75"	60	1.80	100	20	150x280
KST300/12	KST300/12C	12	300	.5	12	0.01	0.35	3.74	80	3.74"	80	2.29	100	20	150x350
KST400/12	KST400/12C	15.75	400	.5	12	0.01	0.35	4.13	105	4.45"	113	2.86	100	15	150x410
KST450/12	KST450/12C	17.75	450	.5	12	0.01	0.35	4.53	115	4.53"	115	3.67	100	10	150x500
KST600/12	KST600/12C	24	610	.5	12	0.01	0.35	5.91	150	5.91"	150	4.40	100	5	230x430
KST700/12	KST700/12C	29.5	750	.5	12	0.01	0.35	7.87	200	7.87"	200	5.41	100	5	300x430
KST800/12	KST800/12C	39.25	1000	.5	12	0.01	0.35	11.81	300	11.81"	300	7.22	100	5	300x430

Hayata Application Tools: CT-3, CT-4, CT-5,* BT9000, BT15000 or By Hand

Applications: General Bundling

Approvals: DNV Approved, ABS Type Approval, cUL Listed.

*CT-5 works with 250 lb. uncoated ties only.