

## RELEASABLE TIES

Hayata releasable cable ties can be used in virtually all indoor, outdoor and underground (including direct burial) applications. They are well-suited for network bundling of data and power cables. Their high strength, non-flammability and rounded edges provide the definitive support for network cables.

All coated ties are 316 grade stainless steel for excellent resistance to temperature extremes, corrosion, weather, chemicals, salt sprays and UV radiation. Non-toxic, halogen-free.

- No water absorption / Non-flammable
- Uncoated temperature range: -112°F (-80°C) to 1000°F (538°C)
- Coated temperature range: -112°F (-80°C) to 302°F (150°C)
- Excellent chemical and UV resistance

- Excellent chemical and UV resistance
- Can be used for air handling spaces
- Radiation resistance: 2 x 108 rads
- Sharp edges and burrs have been removed to protect installation and bundle



## Releasable Ties 75 Lb. Single Wrap / 300 Lb. Double Wrap 316 SS









UNCOATED	COATED	LENGTH		WIDTH		THICKNESS UNCOATED		THICKNESS COATED		BUNDLE Diameter		BAG	P Ties	ACKAG Bags	ING
Part No.	Part No.	In	mm	In	mm	In	mm	In	mm	Min	Max	Wt. Ibs	Per Bag	Per Box	Bag (LxWmm)
KRCT150/6	KRCT150/6C	6	150	.19		0.02	0.5	0.02	0.61	1.4"	36	0.81	100	25	300x190
KRCT230/6	KRCT230/6C	9	230	.19	5	0.02	0.5	0.02	0.61	2.3"	60	1.25	100	20	300x190
KRCT305/6	KRCT305/6C	12	305	.19	5	0.02	0.5	0.02	0.61	3.7"	95	1.76	100	10	500x190
KRCT450/6	KRCT450/6C	17.7	450	.19	5	0.02	0.5	0.02	0.61	5.1"	130	2.4	100	20	600x190
KRCT610/6	KRCT610/6C	24	610	.19	5	0.02	0.5	0.02	0.61	7.2"	185	3.3	100	5	750x190

**Hayata Application Tools:** CT-4 or By Hand **Applications:** Reusable, General Bundling

Approvals: cUL Listed, Coated Releasable ties are DNV Approved, ABS Type Approval, Lloyds Type Approval



## Releasable Ties 250 Lb. Single Wrap / 450 Lb. Double Wrap 316 SS

Custom Colors Available – Call for quote!









UNCOATED	COATED	LENGTH		WIDTH		THICKNESS						DAO	PACKAGING		
						UNCOATED		COATED		DIAMETER		BAG Wt.	Ties Per	Bags Per	Bag
Part No.	Part No.	In	mm	In	mm	In	mm	In	mm	Min	Max	lbs	Bag	Box	(LxWmm)
KRCT150/10	KRCT150/10C	6	150	.39	10	0.02	0.5	0.02	0.61	1.4"	36	1.69	100	10	230x250
KRCT230/10	KRCT230/10C	9	230	.39	10	0.02	0.5	0.02	0.61	2.3"	60	2.51	100	10	230x380
KRCT305/10	KRCT305/10C	12	305	.39	10	0.02	0.5	0.02	0.61	3.7"	95	3.74	100	10	230x480
KRCT450/10	KRCT450/10C	17.7	450	.39	10	0.02	0.5	0.02	0.61	5.1"	130	5.1	100	5	230x600
KRCT610/10	KRCT610/10C	24	610	.39	10	0.02	0.5	0.02	0.61	7.2"	185	6.93	100	10	230x760
KRCT762/10	KRCT762/10C	30	762	.39	10	0.02	0.5	0.02	0.61	9.2"	236	8.69	100	5	230x910
KRCT914/10	KRCT914/10C	36	914	.39	10	0.02	0.5	0.02	0.61	10.6"	270	10.34	100	5	230x1060

**Hayata Application Tools:** CT-4 or By Hand **Applications:** Reusable, General Bundling