

ZIG ZAG TIES

Hayata's Zig Zag stainless steel cable ties are designed to maintain tension on hard surfaces such as a pipe or steel pole. All Zig Zag ties are 316 grade stainless steel for excellent resistance to temperature extremes, corrosion, weather, chemicals, salt sprays and UV radiation.

- Resistance to chemicals and salt sprays
- Non-toxic, halogen-free

Cable ties designed to maintain tension, like banding, on hard surfaces such as a pipe or steel poles



Zig Zag Ties • 200 Lb. • 316 SS



UNCOATED Part No.	COATED Part No.	LENGTH		WIDTH		THICKNESS UNCOATED		THICKNESS COATED		BUNDLE DIAMETER		BAG Wt. lbs	Ties Per Bag	Bags Per Box	Bag (LxWmm)
		In	mm	In	mm	In	mm	In	mm	Min	Max				
TBC200Z	TBC200ZC	8	200	0.18	4.5	0.01	0.26	0.01	0.33	2"	50	0.57	100	50	255X150
TBC360Z	TBC360ZC	14	360	0.18	4.5	0.01	0.26	0.01	0.33	4"	100	0.92	100	35	410X150
TBC520Z	TBC520ZC	20.5	520	0.18	4.5	0.01	0.26	0.01	0.33	6"	150	1.23	100	25	580X150
TBC680Z	TBC680ZC	26.5	680	0.18	4.5	0.01	0.26	0.01	0.33	8"	200	1.54	100	15	430X230
TBC840Z	TBC840ZC	33	840	0.18	4.5	0.01	0.26	0.01	0.33	10"	250	1.91	100	10	430X230
TBC1000Z	TBC1000ZC	39	1000	0.18	4.5	0.01	0.26	0.01	0.33	12"	300	2.29	100	10	430X230
TBC1200Z	TBC1200ZC	47	1200	0.18	4.5	0.01	0.26	0.01	0.33	14"	365	2.73	100	10	430X230
TBC1400Z	TBC1400ZC	55	1400	0.18	4.5	0.01	0.26	0.01	0.33	17"	425	3.17	100	10	430X230



Zig Zag Ties • 350 Lb. • 316 SS



UNCOATED Part No.	COATED Part No.	LENGTH		WIDTH		THICKNESS UNCOATED		THICKNESS COATED		BUNDLE DIAMETER		BAG Wt. lbs	Ties Per Bag	Bags Per Box	Bag (LxWmm)
		In	mm	In	mm	In	mm	In	mm	Min	Max				
TBC200HZ	TBC200HZC	8	200	0.31	4.5	0.01	0.26	0.01	0.33	2"	50	1.12	100	25	255X150
TBC360HZ	TBC360HZC	14	360	0.31	4.5	0.01	0.26	0.01	0.33	4"	100	1.69	100	20	410X150
TBC520HZ	TBC520HZC	20.5	520	0.31	4.5	0.01	0.26	0.01	0.33	6"	150	2.2	100	15	580X150
TBC680HZ	TBC680HZC	26.5	680	0.31	4.5	0.01	0.26	0.01	0.33	8"	200	2.82	100	10	430X230
TBC840HZ	TBC840HZC	33	840	0.31	4.5	0.01	0.26	0.01	0.33	10"	250	3.39	100	5	430X230
TBC1000HZ	TBC1000HZC	39	1000	0.31	4.5	0.01	0.26	0.01	0.33	12"	300	3.89	100	5	430X230
TBC1200HZ	TBC1200HZC	47	1200	0.31	4.5	0.01	0.26	0.01	0.33	14"	365	4.49	100	5	430X230
TBC1400HZ	TBC1400HZC	55	1400	0.31	4.5	0.01	0.26	0.01	0.33	17"	425	5.15	100	5	430X230

Hayata Application Tools: CT-3, CT-5, CT-7, BT2000, BT9000, BT15000 or By Hand
Applications: Where tension on solid object must be maintained – Pipes, Poles, etc.
Approvals: ABS Type Approval